GCCS/DII COE System Integration Support

DII COE Segment Installation Procedures (for IRCS Version 1.0.0.3/2.8.21 for HP-UX 10.20)

June 13, 1997

Prepared for:

DISA/JEJA ATTN: Claire Burchell 45335 Vintage Park Plaza Sterling, VA 20166-6701

Contract Number: DCA100-94-D-0014 Delivery Order Number: 330, Task 6 CDRL Number: A005

Prepared by:

Computer Sciences Corporation
Defense Enterprise Integration Services
Four Skyline Place
5113 Leesburg Pike, Suite 700
Falls Church, VA 22041

THIS DOCUMENT IS UNCLASSIFIED

DII.30.FNL.HP-UX10.20.IRCS.IP

Defense Information Infrastructure (DII)

Common Operating Environment (COE)

Segment Installation Procedures for Internet Relay Chat Server (IRCS) Version 1.0.0.3/2.8.21 (HP-UX 10.20)

June 13, 1997

Prepared for:

DISA/JEJA ATTN: Claire Burchell 45335 Vintage Park Plaza Sterling, VA 20166-6701

Prepared by:

Computer Sciences Corporation
Defense Enterprise Integration Services
Four Skyline Place
5113 Leesburg Pike, Suite 700
Falls Church, VA 22041

Table of Contents

Prefac	e	• • • • • • • • • • • • • • • • • • • •		. 11
1. In:	stallatio	n Procedures (IP) for I	RCS	. 1
	1.1			
1.1.1	Identif	ication		. 1
	1.2	System Overview		. 1
2. Re	eference	d Documents		. 1
3. Sy	stem Er	nvironment		. 2
	3.1	System Requirements		. 2
3.1.1	Hardw	are Requirements		. 2
3.1.2	.2 Operating System Requirements			
3.1.3	Kernel	Requirements		. 2
	3.2	System and Site Preparent	arations	. 2
3.2.1	Systen	n Configuration		. 3
3.2.2	Operation System Preparation			. 3
3.2.3	2.3 Tape/Disk Preparation			
4. In:				
	4.1		dures	
	4.2		es	
4.2.1	Installi	2		
		4.2.1.1	Pre-Installation Instructions	
		4.2.1.2	Re-Installation Instructions	
		4.2.1.3	Installation Walkthrough	
4.2.2	De-Installing the IRCS Segment			
		4.2.2.1	De-Installation Instructions	
		4.2.2.2	Post De-installation Instructions	
	4.3		les	
	4.4			
	4.5 Initializing the Software			. 9
	4.6	6		
	4.7	Important Considerat	ions	. 9
5. No	otes			. 9
Δ Δ	nnendic	es		g

Preface

The following conventions are used in this document:

Bold Used for information that is typed, pressed, or selected in executables

and instructions. For example, select connect to host.

Italics Used for file names, directories, scripts, commands, user IDs, document

names, and Bibliography references; and any unusual computerese the

first time it is used in text.

<u>Underline</u> Used for emphasis.

Arrows <> Used to identify keys on the keyboard. For example <Return>.

"Quotation Marks" Used to identify informal, computer-generated queries and reports, or

coined names; and to clarify a term when it appears for the first time.

For example "Data-Generation Report."

Courier Font Used to denote anything as it appears on the screen or command lines.

For example tar xvf dev/rmt/3mm.

Capitalization Used to identify keys, screen icons, screen buttons, field, and menu

names.

1. Installation Procedures (IP) for IRCS

This document provides a quick reference for installing the Internet Relay Chat Server (IRCS) segment for the Defense Information Infrastructure (DII) on HP-based machines.

1.1 Scope

1.1.1 Identification

This section contains identification information for the IRCS segment:

Segment Name: Internet Relay Chat Server

Segment Type: Software Prefix: IRCS

Home Directory: /h/COE/Comp/IRCS

Distribution Type: This software requires no licenses

Version Number: 1.0.0.3/2.8.21

Platform: HP (UNIX) Workstation/HP-UX 10.20.

1.2 System Overview

This section contains system overview information for the IRCS segment:

Purpose: An IRC server application is an on-line Internet/Secret Internet Protocol

Router Network (SIPRNET) conferencing application which transmits messages and commands between IRC client applications, allowing

messages entered by users via these applications to be viewed by other IRC

client users within seconds.

Usage: Provides similar capabilities as the "Comm" portion of WIN

Teleconferencing and may be used to provide real-time, conferencing

capabilities over the SIPRNET to the warfighter.

References: Reference documentation: See related documents which can be found in

the /man sub-directory of this segment.

2. Referenced Documents

Soft copies of the following documents can be found in the *IRCS/man* sub-directory of this segment:

- C Admin
- C Manual
- C Networking

- C Operators.
- C DII COE Segment System Version Description (SVD) Internet Relay Chat Server (IRCS) for V1.0.0.3/2.8.21 delivered with this segment.
- C DII COE Segment Software Test Description (STD) Internet Relay Chat Server (IRCS) for V1.0.0.2/2.8.21.

3. System Environment

3.1 System Requirements

This section lists the system requirements for the IRCS segment.

3.1.1 Hardware Requirements

The following hardware requirements have been identified for testing the integration of the IRCS segment:

HP Platform

C IRCS V1.0.0.3/2.8.21

C OS: HP-UX 10.20 C DISK: 1873 KB C MEMORY: 32000 KB

3.1.2 Operating System Requirements

The operating system required for testing the integration of the IRCS segment is HP Platform, HP-UX 10.20.

3.1.3 Kernel Requirements

The DII COE kernel version required for testing the integration of the IRCS segment is V3.0.1.0 for HP-UX 10.20.

3.2 System and Site Preparations

Before installing this version of IRCS, the *irc* user account must be added to your system using HP's system administration utility, "SAM". This allows your system to create a "password" file for this user which is required by the IRC server daemon. Refer to Subsections 4.2.1.1 and 4.2.2.2 for details on how to add and remove this user via the SAM utility.

3.2.1 System Configuration

None.

3.2.2 Operation System Preparation

None.

3.2.3 Tape/Disk Preparation

Rewind the tape before beginning the installation process.

4. Installation Instructions

4.1 Media Booting Procedures

None.

4.2 Installation Procedures

4.2.1 Installing the IRCS Segment

This section describes the procedures necessary to install and de-install the IRCS segment. If you are installing this segment for the first time, refer to Subsection 4.2.1.1. If you are re-installing this segment, refer to Subsections 4.2.1.1 and 4.2.1.2.

4.2.1.1 Pre-Installation Instructions

The IRCS segment should be installed on the application server machine for your site.

When using the Segment Installer to install this segment, pay close attention to, and follow all instructions provided. Make note of any warning messages that may appear during the course of the installation.

NOTE: Help information is provided for some of the prompts displayed. You may access help information by entering a "?" where indicated.

The *irc* user must be added to your system using the HP SAM utility so that the required password file may be created for this user. The following describes how this should be done:

- Step 1: Bring up an x-term or dtterm window and "su" to user *root*.
- Step 2: Run the HP system administration utility, SAM by typing /usr/sbin/sam <ENTER> at the command line.

- Step 3: Wait for the System Administration Manager window to be displayed.
- Step 4: Double-click on the **Accounts for Users and Groups** icon.
- Step 5: Double-click on the **Users** icon.
- Step 6: From the Actions menu, select the **Add** option.
- Step 7: When the Add a User Account dialog box appears, do the following:
 - C Enter irc in the LOGIN NAME: field
 - C Enter 219 in the USER ID (UID): field
 - Enter /user/irc in the HOME DIRECTORY: field. Make sure that the Create Home Directory checkbox which appears to the right of this field is selected.
 - C Enter mail in the PRIMARY GROUP NAME: field
 - C Enter irc daemon in the REAL NAME: field.
- Step 8: Press the **OK** button to save the information entered and to exit the dialog box.

NOTE: A dialog box may be displayed informing you of the authorization number which has been generated for the *irc* user. Be sure to make note of this authorization number.

Step 9: When the Confirmation Window is displayed, click the **YES** button.

4.2.1.2 Re-Installation Instructions

If you are re-installing this segment in order to replace an older version of the Internet Relay Chat Server and, if you wish to save the older IRC server configuration, perform the following steps:

- Step 1: Before de-installing the older version of the IRCS segment, copy the /h/COE/Comp/IRCS/lib/ircd/ircd.conf file to a temporary location. Also, make note of your IRC server's current server type (i.e., a "leaf" or "hub").
- Step 2: De-install the older IRCS segment.

Step 3: Install V1.0.0.3/2.8.21 of the IRCS segment. Then, specify whether your server is a leaf or a hub. Be sure to specify default values when prompted. Leave text entry fields "blank", and reply "no" when asked to specify IRC operators and neighbors.

NOTE: Your server type specification must match that of your server's previous configuration.

- Step 4: Copy the *ircd.conf* file saved in your temporary location back into the /h/COE/Comp/IRCS/lib/ircd sub-directory.
- Step 5: Lastly, re-start your IRC server by executing the following commands:

/h/COE/Comp/IRCS/lib/stop (to shut-down the server)
/h/COE/Comp/IRCS/lib/start (to start-up the server).

Your previous IRC server's configuration has now been restored.

4.2.1.3 Installation Walkthrough

The following is a brief walkthrough of the installation procedures for the IRC Server:

Step 1: * * * IRC Server Installation Routine * * *

Carefully read the initial instructions displayed and press <Enter> to continue.

Step 2: * * * IRC Server Type Specification * * *

When prompted, type **leaf** or **hub** to specify your server as a leaf or hub server respectively. If you are not sure whether or not your server is a hub or a leaf, then accept the default of leaf.

Step 3: * * * IRC Server Host Configuration * * *

If the machine configuration information displayed is not correct for your machine type **n** and press <Enter>. This will terminate the installation procedures allowing you to check your machine's configuration and make necessary modifications.

If the machine configuration information displayed is corrected, press <Enter>.

If another IRC server has been located in your domain and you wish establish another server in your domain, type **y** and press <Enter> when prompted.

When prompted, enter the correct server name for your IRC server if the default server name specified is not correct. (If your machine has an Domain Name Server [DNS] alias with the prefix *irc*, enter the full DNS alias name here.)

Step 3: * * IRC Server Administration Specification * *

When prompted, enter the name of your facility (e.g., "Kiesler AFB") and press <Enter>.

Next, enter a brief functional description of your server (must be 65 characters or less). This description should indicate how the server will be used on the network (e.g., "Hub Server for SE USA").

Next, enter the name, e-mail address, and/or telephone number of the person who can provide technical assistance to users accessing this server.

Step 4: * * * IRC SERVER OPERATOR SPECIFICATION * * *

NOTE: IRC Operators need not be specified for leaf servers. Therefore, this routine may be by-passed for leaf servers, if desired.

The IRC Operator nickname is "oper" by default. The *ircd.conf* file can be edited if a different nickname is desired.

- a) When asked whether or not you wish to specify IRC operators at this time, type **y** and press <Enter>, to proceed with specifying IRC operators. However, to by-pass this outline, press <Enter> (default response is "n") to continue to the next routine.
- b) When prompted, press <Enter> to allow operators to connect to your server from any machine in your server's domain.
- c) If you do not want operators to connect to your server from any machine in your server's domain, enter the machine name or IP address of the machine from which they can connect to your server as operators. (You may use wild cards for the machine name or IP address to specify multiple machines.)

- d) When prompted, enter a non-null, authentication code (8 characters or less) that IRC operators will use to authenticate themselves on client machines.
- e) Repeat Steps 4b and 4c to specify additional client machines that IRC operators may use to access the server.
- f) To exit this routine, leave the Machine Name or IP Address field blank and press <Enter>.

Step 5: * * * IRC SERVER NEIGHBORS SPECIFICATION * *

Neighboring IRC Servers should only be specified after <u>all</u> of the information specified in the "Pre-Installation Instructions" section of this document has been obtained for a particular site.

NOTE:

IRC Neighbor Servers need not be specified at time of installation. Therefore, this routine may be by-passed, if desired. You may execute the following routine to specify neighboring IRC servers at a later time:

/h/COE/Comp/IRCS/bin/IRCS_verify add_neighbors

- a) When asked whether or not you wish to specify IRC neighbors at this time, type **y** and press <Enter>, to proceed with specifying IRC neighbors. However, to by-pass this operation, press <Enter> (default response is "n") to continue to the next routine.
- b) When prompted, type y and press <Enter> to obtain more information on how to specify IRC neighbors. Or, press <Enter> (default response is "n") to continue.
- c) When prompted, enter the name of the machine hosting your neighbor's IRC server.
- d) Enter your neighbor's IRC server name (that is, the IRC server name your neighbor used or will use when installing their IRC server).
- e) Enter a non-null, authentication code (8 chars or less) that your server will use to access your neighbor's server.
- f) Enter a non-null, authentication code (8 chars or less) that your neighbor will use to access your server.

- g) When asked whether or not your neighbor's server is a hub, press <Enter> (default response is "y") to respond "yes" or, type **n** and press <Enter> to respond "no".
- h) Repeat Steps 5a to 5e to specify additional neighboring IRC servers.
- i) To exit this routine, leave the Neighbor's Host Machine Name field blank and press <Enter>.
- Step 6: * * * IRC Server Automatic Start-up * * *

Make note of all pertinent information that appears in this display window and respond to subsequent prompts accordingly.

4.2.2 De-Installing the IRCS Segment

4.2.2.1 De-Installation Instructions

To de-install the IRCS segment, select the IRCS segment from the COE Installer's Currently Installed Segments window and press the **DEINSTALL SOFTWARE** button.

4.2.2.2 Post De-installation Instructions

After the IRCS segment has been de-installed, you will need to remove the *irc* user via the HP's SAM utility. To do this, perform the following steps:

- Step 1: Bring up an x-term or dtterm window and "su" to user *root*.
- Step 2: Run the HP system administration utility, SAM, by typing /usr/sbin/sam <ENTER> from the command line.
- Step 3: Wait for the System Administration Manager window to be displayed.
- Step 4: Double-click the **Accounts for Users and Groups** icon.
- Step 5: Double-click the **Users** icon.
- Step 6: When the Accounts for Users and Groups window is displayed, locate and select (i.e., single-click on) the **irc** user.
- Step 7: From the Actions menu, select the **Remove** option.
- Step 8: When the Remove a User dialog box is displayed, make sure the Removed from User's Home Directory Only file removal option is selected and press the **OK** button.

4.3 Installation of Upgrades

None.

4.4 Installation Verification

To verify that this software has been installed correctly, refer to the procedures outlined in the *DII COE Segment Software Test Description (STD)* - *Internet Relay Chat Server (IRCS)* document that was delivered with V1.0.0.2/2.8.21 of this segment.

4.5 Initializing the Software

Not required.

4.6 List of Changes and Enhancements

Refer to the "Changes Installed" section of the *DII COE Segment System Version Description* (SVD) - Internet Relay Chat Server (IRCS) document for V1.0.0.3/2.8.21, for details regarding changes incorporated into this release of the IRCS segment.

4.7 Important Considerations

None.

5. Notes

None.

A. Appendices

None.